

	IT	Modello:	<h1>Stg Fcm</h1>	Trasporto e movimentazione alimenti
	ENG	Model:		<i>Foodstuff carriage</i>

Italiano



Litri	∅ mm.	Altezza cilindro (mm)	Altezza gambe (mm)	Altezza totale (mm)	N° gambe	N° ruote	∅ ruote (mm)	Spessore cilindro (mm)	Spessore fondo (mm)	Spessore tetto (mm)	Spessore gambe (mm)	Scarico totale	Prezzo di listino senza portella Euro
-------	----------	--------------------------	-----------------------	------------------------	----------	----------	--------------	---------------------------	------------------------	------------------------	------------------------	-------------------	---

English



Liters	∅ mm.	Height cylinder (mm)	Height legs (mm)	Height total (mm)	N° legs	N° castor	∅ castor (mm)	Thickness cylinder (mm)	Thickness bottom (mm)	Thickness roof (mm)	Thickness legs (mm)	Total drain	List price without door Euro
--------	----------	-------------------------	---------------------	----------------------	---------	-----------	---------------	----------------------------	--------------------------	------------------------	------------------------	----------------	--

300	720	750	400	1400	3	3	150	1,2	1,5	1,5	2	Din 40	
400	720	1000	400	1650	3	3	150	1,2	1,5	1,5	2	Din 40	
500	796	1000	400	1650	3	3	150	1,2	1,5	1,5	2	Din 40	
700	930	1000	400	1650	3	3	150	1,2	1,5	1,5	2	Din 40	
1000	1150	1000	400	1650	3	3	150	1,2	1,5	1,5	2	Din 40	

Optional: portella - door

Portella Door ∅ 300	Portella Door ∅ 400	Portella rettangolare Rectangular door 310x420		
				



Caratteristiche:

- Serbatoi costruiti in acciaio inox aisi 304 18/10 (su richiesta in acciaio inox aisi 316)
- Finitura interna lucida a specchio con saldature satinare, finitura esterna fioretata con saldature satinare
- Fondo conico 10°
- Chiusino superiore ∅ 400 altezza telaio 90mm apertura laterale e bandiera con sfiato in pvc
- Valvola in acciaio inox aisi 304 con attacco DIN 40 MG/ 40 Garolla
- Ruote ∅ 150 in acciaio inox girevoli con freno



Features:

- Stainless steel tanks made in AISI 304 (on demand AISI 316)
- Bright annealed inside with satin welding, marble outside with satin welding
- Conical bottom 10°
- Upper lid antirritention ∅ 400mm, lateral flag opening, frame height 90mm
- Ball valve in stainless steel DIN40MG/40 Garolla
- Castor ∅ 150 made in stainless steel with brake

